



RETURN AIR REQUIREMENTS

- ① 20"x16" GRILL REQUIRED
- ② 4"x10" GRILL W/ 2 1/2" DOOR UNDERCUT
- ③ DOOR(S) MUST BE UNDERCUT 2 1/2" MIN.
- ④ 4"x24" OR 6"x14" GRILL REQUIRED

INDICATES REQUIRED NUMBER OF STUDS IN COLUMN
THE * SPECIFIES THAT THERE CAN BE NO HOLES IN STUDS IN COLUMNS

BRAND
SCHULT

SERIES
MH32

CMH MANUFACTURING, INC.

REVISIONS	BY	DATE	GENERAL NOTES
UPDATED TO 2009 SPECS	SSM	12/22/08	Ceiling Height = 90.00
REVERSED WASHER/DRYER LOCATIONS	SSM	03/21/07	REFER TO DAPIA PAGE MMP-2.0 FOR AREA LIGHT & VENT
			REFER TO DAPIA PAGE EL-1.2 FOR ELEC. SYMBOL & BRANCH CIRCUIT NUMBER
			FLOOR FRAMING SPACING = 16
			TOTAL WINDOW SQFT = 121.8

DRAWING TITLE
MASTER PLAN

MODEL NAME TIMBERLAND-365442		SQ. FT. 1920	
PLANT 954	DESCRIPTION 32X64 3BR-2BA	MODEL NO. R6432-43	
DRAWN BY CLD	ORIG. DATE 04/21/2014	DATE PRINTED 06/14/2014	SHEET NO. 1-1